

Xerox® Phaser® 6500 Colour Printer and WorkCentre™ 6505 Colour Multifunction Printer The right colours, the easy way



Phaser[®] 6500 Colour Printer and WorkCentre[™] 6505 Colour Multifunction Printer

The right solution for today's pace of business. Your busy workteam needs a value-packed colour device that gets the job done with the rare combination of outstanding print quality, unparalleled simplicity, and day-in, day-out dependability. Introducing the Phaser 6500 and WorkCentre 6505.



The colours your business needs

The Phaser 6500 colour printer and WorkCentre 6505 colour multifunction printer give your important documents a powerful, colourful boost.

- **Outstanding print quality.** A print resolution of up to 600 x 600 x 4 dpi makes your printed communications stand out and grab attention.
- True Adobe[®] PostScript[®] 3[™]. Count on consistently precise print jobs with bright, true colours and superior graphics.
- Advanced toner technology. Xeroxexclusive EA Toner uses particles engineered for uniform size and shape, producing superior image detail and line definition, and text that's sharp and clear.
- Always the right colour. PANTONE[®] Colour approved solid-colour simulations and Xerox colour correction technology ensure results that match your expectations.

Ready to help

We designed the Phaser 6500 and WorkCentre 6505 as simple colour devices that support single users and small workteams.

- **Print and go.** Work quickly with print speeds of up to 23 ppm for colour and black and white.
- More productivity for more people. Connect and go, thanks to built-in networking and seamless compatibility with mixed-user environments, including PC, Macintosh and Linux.
- Easy management. With Xerox CentreWare[®] IS, remote device administration is handled with ease right from your computer's browser.
- **Out of colour toner?** Our Run Black feature lets you continue printing with black until you can replace toner.
- Total peace of mind. Our standard one-year on-site warranty.

Easy on your environment

The Phaser 6500 and WorkCentre 6505 help you meet today's environmental challenges.

- Print more, use less. Whether you choose manual two-sided printing or upgrade to convenient automatic duplexing, you'll conserve paper for reduced costs and lowers environmental impact.
- **Toner-only cartridges.** With minimal packaging, our toner-only cartridges allow for 80% less waste than comparable colour devices using integrated print cartridges.
- A perfect fit. Both devices feature a small footprint, which allows for easy integration within your work space, whether on your desk or in a shared location.
- The quiet partner. Engineered for extraquiet operation to minimise impact on busy offices.
- **Consolidate and save.** The value-packed WorkCentre 6505 multifunction printer will save on energy and supplies costs by combining the functions of multiple devices into one.

Phaser® 6500 Quick Facts

- Print up to 23 ppm colour and black and white
- 600 x 600 x 4 dpi
- Optional automatic two-sided printing*
- Powerful 400 MHz processor
- Robust 40,000 pages/month duty cycle
- 256 MB memory, expandable to 768 MB
- First page out time of 13 seconds colour, 12 seconds black and white

* Standard on DN configuration



WxDxH: 404 x 426 x 416 mm



Productivity, accelerated. The WorkCentre 6505 colour multifunction printer builds on the outstanding print performance found in the Phaser 6500, delivering a host of powerful productivity tools designed to make your daily office tasks more efficient than ever.



The WorkCentre 6505 includes an intuitive front panel for configuring device settings and programming jobs.

2

A 35-sheet automatic document feeder handles media sizes from 139.7 x 139.7 mm to 216 x 356 mm

3

A front-side USB port allows users to quickly print from or scan to any standard USB memory device.

4

Powerful scanning capabilities include Scan to Email, Network Scanning, Direct Scan to Applications including Optical Character Recognition, and Scan to USB memory device.

6

Standard copy features include ID Card Copy, N-up, auto fit, cloning, collate and more.

6

Send faxes from the network using LAN Fax, or take advantage of full walkup fax features such as speed dial, remote receive and fax broadcast.

0

A standard 533 MHz processor and 256 MB memory (expandable to 768 MB) let the WorkCentre 6505 easily handle a heavy workload — even a steady stream of pages with graphics, photos and charts.

Optional 250-sheet paper tray increases capacity to 500 sheets — enough to load a full ream of paper.





- Print up to 23 ppm colour and black and white
- 600 x 600 x 4 dpi
- Optional automatic two-sided printing*
- Powerful 533 MHz processor
- Robust 40,000 pages/month duty cycle
- 256 MB memory, expandable to 768 MB
- First page out time of 12 seconds colour, and black and white
 *Standard on DN configuration



Phaser[®] 6500 and WorkCentre[™] 6505

		Phaser 6500N	Phaser 6500DN	WorkCentre 6505N	WorkCentre 6505DN		
Speed		Up to 23 ppm colour and black and white					
Duty Cycle		Up to 40,000 pages / month ¹					
Paper Handling Paper input	Standard	NA			Automatic Document Feeder (ADF): 35 sheets: Custom Sizes: 139.7 x 139.7 mm to 216 x 356 mm		
		Manual Feed Slot: 1 sheet; Custom sizes: 76 x 127 mm to 216 x 356 mm					
		Tray 1: 250 sheets; Custom sizes: 76 x 127 mm to 216 x 356 mm					
	Optional	Tray 2: 250 sheets; Custom sizes: 148 x 210 mm to 216 x 356 mm					
Paper output		150 sheets face down					
Automatic two-sided pri	nting	Optional	Standard	Optional	Standard		
Print First-page-out-time		As fast as 13 seconds colour / 1	2 seconds black and white	As fast as 12 seconds col	As fast as 12 seconds colour / 12 seconds black and white		
Resolution (max)		Up to 600 x 600 x 4 dpi					
Processor		400 MHz		533 MHz	533 MHz		
Memory (std / max)		256 MB / 768 MB					
Connectivity		USB 2.0, 10/100/1000 Base-T Ethernet					
Page description languages		Adobe® PostScript® 3 [™] , PCL® 6 emulation					
Print features	Standard	PANTONE® Colour approved solid-colour simulations, N-up, Fit to page, Booklet printing, Skip blank pages, Run black, Covers/Separators ² , Poster Watermarks ² , Overlays ² , Banner sheets ² , Draft mode ²					
Option		³ Secure print, Proof print, Personal print, Saved print, RAM collation					
Copy First-copy-out-time				As fast as 20 seconds co	olour / 13 seconds black and white		
Copy resolution		- NA		600 x 600 dpi	600 x 600 dpi		
Copy features					1 sided to 2 sided copying ⁴ , Reduce/enlarge (25%-400%), N-up copying, Auto fit, Cloning, Collation, ID Card Copy, Edge erase		
Fax Fax features ⁵		NA		Lighter / darker, Polling, protection, Fax forwardi	33.6 Kbps with MH/MR/MMR/JBIG/JPEG compression, Secure fax receive ⁴ , Lighter / darker, Polling, Remote receive (with external phone), Junk fax protection, Fax forwarding, Delay send, Broadcast, Address book (up to 200 speed dials, 6 group dials), Resolution up to 400 x 400 dpi, LAN Fax (Send)		
Scan Scan destinations		NA		via FTP (server) and SM	Scan to Email (local address book or LDAP integration), Network Scanning via FTP (server) and SMB (server or computer), Direct Scan to Applications including OCR, USB Memory Device		
Scan features					resolution, 24-bit colour / 8-bit greyscale, e and multi-page) / XDW		
Security		Secure HTTPS (SSL), IPsec, 802.1x Authentication, IPv6, SNMPv3, Audit Log, IP Filtering					
Warranty		One-year on-site warranty					

Device Management

CentreWare® Internet Services, CentreWare Web, PrintingScout™, Email alerts , Apple® Bonjour

Print Drivers

Windows® XP, Vista, Server 2003, Server 2008, 7; Mac OS® version 10.5 and higher; Linux, Xerox Global Print Driver®, Xerox Mobile Express Driver™

Media Handling

Automatic Document Feeder**: 50 – 125 gsm; Manual Feed Slot and Trays: 60 – 216 gsm; Media types: Plain paper, glossy, business cards, envelopes, labels, cardstock

Operating Environment

Temperature: Storage: -20° to 40° C; Operating: 10° to 32° C; Humidity: 10% to 85%; Sound pressure levels: 6500: Printing (Enhanced): 53 dB(A), Standby: 25 dB(A); 6505: Printing (Enhanced): 52 dB(A), Standby: 22 dB(A); Sound power levels: Printing (Enhanced): 6500: 6.73 B, Standby: 3.86 B; 6505: 6.63 B, Standby: 3.65 B; Warm-up time (from sleep mode): as fast as 31 seconds

Electrical

Power: 110-127 VAC, 50/60 Hz or 220-247 VAC, 50/60 Hz; Power consumption: 6500: Standby: 55 W, Printing: 375 W, Sleep: 15 W; 6505: Standby: 65 W, Printing: 425 W, Sleep: 18.4 W; ENERGY STAR® qualified

Dimensions (WxDxH)

6500N/DN: 403.5 x 425.5 x 415.6 mm; Weight: 6500N: 18.2 kg; 6500DN: 19.4 kg; 250-sheet feeder: 400 x 457 x 107 mm; Weight: 4.4 kg; 6505N/DN: 430 x 544.2 x 584.4 mm; Weight: 6505N: 28.4 kg; 6505DN: 29.6 kg; 250-sheet feeder: 419.2 x 518 x 107 mm; Weight: 4.5 kg

Certifications

FCC Part 15, Class B, FCC Part 686, UL 60950-1/CSA 60950-1-07, 2nd Edition, CE Mark applicable to Low Voltage Directive (2006/95/EC), EMC Directive (2004/108/EC), and R&TTE Directive (1999/5/EC) 6, GOST, NOM, GS Mark, Citrix Ready, Section 508 (compliant with minor exceptions), ENERGY STAR[®] qualified

Supplies

Jupplies	
High-capacity Print Cartridges*:	
Black: 3,000 std. pages	106R01604
Cyan: 2,500 std. pages	106R01601
Magenta: 2,500 std. pages	106R01602
Yellow: 2,500 std. pages	106R01603
Standard-capacity Print Cartridges*:	
Cyan: 1,000 std. pages	106R01598
Magenta: 1,000 std. pages	106R01599
Yellow: 1,000 std. pages	106R01600
Options	
250-sheet feeder for Phaser 6500	097504070
250-sheet feeder for WorkCentre 6505	097S04264
Productivity Kit	097S04269
Duplex unit	097504069
Wireless network adapter	
– European power converter**	097503741
– UK power converter	097503742
* Average standard pages Declared Yield in accordance with ISO/IEC 19798	

* Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

** Not available in Denmark and Switzerland



For more information visit us at www.xerox.com/office

© 2011 Xerox Corporation. All rights reserved. Contents of this publication may not be reproduced in any form without permission of Xerox Corporation. XEROX®, XEROX and Design®, CentreWare®, Phase® and WorkCentre® are trademarks of Xerox Corporation in the U.S. and/or other countries. Adobe® and PostScript® 3^w are registered trademarks or trademarks of Adobe Systems, Incorporated, PCL® is a registered trademark of Hewlett-Packard. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. DERGY STAR and the ENERGY STAR mark are registered U.S. marks. All other trademarks are the property of their respective manufacturers. The information in this brochure is subject to change without notice. 2/11 650BR:011B

